

Product Specifications

| | |
|---------------------------|------------------------|
| Style Number | VV035 |
| Construction | Waterproof Foamed Core |
| Edge Profile | Enhanced Painted Bevel |
| Nominal Dimensions | 9" wide, 72" long |

| | US Units | Metric Units |
|----------------------------------------|-------------------------|--------------|
| Actual Product Width | 8.98" | 23 cm |
| Actual Product Length | 72.05" | 183 cm |
| Wear Layer Thickness | 20 mil (0.02") | 0.5 mm |
| Overall Product Thickness | 0.314" | 8 mm |
| Core Thickness | 0.256" | 6.5 mm |
| Attached Underlayment Thickness | Attached Cork | |
| Attached Underlayment Thickness | 0.059" | 1.5 mm |
| Finish | UV Acrylic | |
| Installation Methods | Floating or Direct Glue | |
| Profile | Angle/Tap | |
| Country of Origin | Imported | |

Packaging

| | | |
|-------------------------|-------------|--------|
| Area per Box | 26.95 sq ft | 3 sq m |
| Pieces per Box | 6 pcs | |
| Weight per Box | 46.3 lbs | 21 kg |
| Boxes per Pallet | 40 boxes | |




912 Hayes Oak

Colors



912 Hayes Oak

Color Variation: V2 - Slight



914 Williamson Oak

Color Variation: V3 - Moderate

Performance

| | |
|-------------------------------------|-----------------|
| Static Load (ASTM F970) | Passes |
| Residual Indentation (ASTM F1914) | Passes |
| Resistance to Heat (ASTM F1514) | Passes |
| Resistance to Light (ASTM F1515) | Passes |
| Resistance to Chemicals (ASTM F925) | Passes |
| Radiant Panel (ASTM E648) | Passes, Class I |
| Slip Resistance (ASTM D2047) | ADA compliant |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

- USF Lifetime
- [Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof](#)
- USF 10 Year Medium Commercial


Certi cations

GreenGuard (Certi cation, Gold, Private Label) Certi ed


Coordinating Trim




Baby Threshold*
01V09 | 94"




T-Molding*
02V37 | 94"
02V40 | 94"
02V44 | 94"
02V45 | 94"
02V46 | 94"
02V47 | 94"
02V48 | 94"
02V50 | 94"




Quarter Round
01V35 | 94"



Overlap Stairnose*
01V83 | 94"



Flush Stairnose
FS7HU | 94"
02V10 | 94"



Overlap Reducer
01V59 | 94"

*Packaged with molding track

Stair Tread



Stair Tread
03Z70 | 48"

