



STONETECH® Stain Protecting Grout Additive

DS-215.5-0724

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

STONETECH® Stain Protecting Grout Additive

2. MANUFACTURER

LATICRETE International, Inc.
1 LATICRETE Park North
Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 1235

Toll Free: 1.800.243.4788, ext. 1235

Fax: +1.203.393.1684

Website: laticrete.com

3. PRODUCT DESCRIPTION

STONETECH® Stain Protecting Grout Additive allows you to grout and seal in one easy step to ensure a lasting stain-resistant finish. Simply add this protectant to grout in place of water, to keep grout color intact and create a grout that blocks oil and water-based stains.

Uses

- Countertops
- Backsplashes
- Floors
- Walls

Advantages

- Grout and seal in one easy step
- Offers protection against oil and water based stains
- Simply replaces water when mixing grout
- Will not alter grout color
- Water-based formula

Suitable Substrates

- Grout

Packaging

US

- ST339-0464: 64oz (1.9L) Bottle - 4 / case
- ST339-0627: 27oz (799ML) Bottle - 6 / case
- ST339-0103: 2.5gal (9.5L) Bottle - 1 unit

CANADA

- ST342-0464: 64oz (1.9L) Bottle - 4 / case

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

Cautions

- Consult SDS for more safety information.
- Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
- Skin contact: Wash skin with soap and water. Get medical attention if symptoms occur.
- Eye contact: Flush eyes thoroughly with water for at least 15 minutes. Get medical attention if symptoms persist.
- Ingestion: Rinse mouth. Do not induce vomiting. Get medical attention if any discomfort continues.
- Storage and Handling Instructions: CAUTION: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. Do not spray. Do not ingest. Avoid contact with eyes and skin. Avoid prolonged exposure to vapors. Use only in a well-ventilated area. KEEP OUT OF REACH OF CHILDREN. Do not freeze or store above 100 °F (38 °C). Do not mix with other chemicals. Do not release into natural waterways.

4. TECHNICAL DATA

VOC/LEED Product Information

8 g/L in product (including water for Low Solids Coatings)

Physical Properties

Form	Liquid
Color	Clear to light yellow
Odor	none
pH	7-9

Working Properties

Full Cure	Follow grout manufacturer's recommended grout dry times.
-----------	--

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

Surface Preparation

Read entire label before using. Use only as directed. Ensure work area is well-ventilated during mixing and until surface is dry. Keep children and pets out of the area until surface use resumes.

Directions

1. Use STONETECH® Stain Protecting Grout Additive instead of water when preparing grout.
2. Prepare grout according to the grout manufacturer's recommended mixing instructions using a grout trowel or low speed mixer to achieve the appropriate grout consistency.
3. Allow the grout to stand (slake) for 10 minutes, re-mix before application.
4. Apply grout in accordance to the grout manufacturer's recommended application instructions.
5. Follow grout manufacturer's recommendations for time to traffic. Protect grout from water immersion or freezing for 10 days, or per grout manufacturer's instructions, whichever is longer.

6. AVAILABILITY AND COST

Availability

LATICRETE materials are available worldwide.

For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at

laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

8. MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the STONETECH sealer used, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH® Stone & Tile Cleaner is recommended. For tough or difficult to remove soil use STONETECH KlenzAll™ Cleaner, a nylon scrubbing pad or a long handled stiff bristle brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 262 Stone and Tile Care Guide.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235

Telephone: +1.203.393.0010, ext. 1235

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at laticrete.com.

10. FILING SYSTEM

Additional product information is available on our website at laticrete.com. The following is a list of related documents:

- DS 230.13: LATICRETE Product Warranty
- DS 211.0: STONETECH Stone & Tile Cleaner
- DS 215.0: STONETECH KlenzAll Cleaner
- TDS 262: Stone and Tile Care Guide

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com

© 2024 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.